



# Case Erector

## CE15

Model CE15-T  
Model CE15-ST



## Product Overview

<b>Speed</b>	<ul style="list-style-type: none"> <li>Up to 15 cases/min</li> </ul>
<b>Case Size Range</b>	<ul style="list-style-type: none"> <li>L 7.5-24in   W 7.5-16in   D 3-18.5in</li> </ul>
<b>Sealing</b>	<ul style="list-style-type: none"> <li>Tape</li> </ul>
<b>Controls</b>	<ul style="list-style-type: none"> <li>Allen-Bradley MicroLogix PLC</li> </ul>
<b>Changeovers</b>	<ul style="list-style-type: none"> <li>Scales, pointers and quick-release handles</li> </ul>
<b>Standards</b>	<ul style="list-style-type: none"> <li>PackML compliant</li> <li>UL® listed control panel</li> </ul>
<b>Construction</b>	<ul style="list-style-type: none"> <li>Heavy duty welded tubular frame</li> <li>Mild steel or stainless steel</li> </ul>
<b>Key Differentiators</b>	<ul style="list-style-type: none"> <li>Dual opposed case erecting</li> <li>Independent articulated magazine pick and score line controlled flap closing</li> </ul>
<b>Machine Size Range</b>	<ul style="list-style-type: none"> <li>L 8ft   W 8ft   H 7ft</li> </ul>
<b>Options</b>	<ul style="list-style-type: none"> <li>Comprehensive integration services</li> </ul>

## Key Benefits

- > Case Size & Style Flexibility
- > Tolerates Variances for Consistently Square Erection
- > Reliable Performance
- > Maximized Uptime & Output
- > User Centric Design
- > PackML Compliance
- > Optimized TCO
- > Complete Integration & Aftermarket Services

## Case Styles



HSC



RSC