



CS15 Case Sealer

Pearson's CS15 Case Sealers handles a wide-range of RSC and CSSC case sizes. Featuring a compact size and continuous motion, the CS15 top seals at speeds of 15 to 29 cases per minute depending on case length. A convenient bypass option eliminates the need for additional conveying when pre-sealed boxes or HSCs are introduced into the line. Spring loaded synchronous compensating side belts and squaring wheels ensure cases remain square throughout the closing and sealing process.



Speed	15-29 cases/min depending on case length	
Min. Case Size Base Machine	6" (L) x 4.5" (W) x 3" (H)	Extended case size range available
Max. Case Size Base Machine	24" (L) x 16" (W) x 18.5" (H)	
Sealing	Tape	
Operation	Pneumatic	
Changeover	Manual, supported by scales, pointers, and quick release handles, 2 min (estimate for trained technician)	
Construction	Mild Steel	
Machine Size Range (ft)	8 (L) x 8 (W) x 7 (H)	
Controls	Allen-Bradley PLC PackML Compliant	
Air Requirements	80 PSI	
Power Requirements	120 VAC	
Disconnect Sizes	16 Amps	
Air Consumption	0.016 SCF/Cycle	
Full Load Amp Base Machine	6 Amps	
Case Support	  RSC CSSC	

Standard Features

- Safety Redundancy with CAT 3
- Easily Accessible Grace Port
- Remote Access Support Capability

Popular Upgrade Options

- Oversized and Undersized Case Support
- Additional Tape Head
- Tape Sensing
- HMI
- Hand Pack Station
- Portability
- Plant Level Ethernet Connection

Resources To view videos or download floorplans of the base machine, please click on the links



CS15
Floorplan



CS15
Floorplan



Standard
Component List



Ewon Remote
Access Router

