





## Semi-Automatic Stretch Wrap System

The Predator XS is designed with extra features that surpass all preconceived notions of performance and value in semi-automatic systems.

The Predator XS provides greater film savings as well as improved performance with Select-Stretch™. Allen-Bradley PLC, automatic film cut, AC drives, and Fast Film Feed makes the Predator XS the most advanced and reliable solution available.



# **HIGHLIGHTS**

- » Select-Stretch™ offers greater film performance with 230% and 270% gears
- » Automatic film cut improves productivity and saves time
- » Allen-Bradley MicroLogix PLC and AC drive system provide greater performance and reliability



## **CONTROL PANEL FEATURES**

- Wrap Direction (Up Only or Up and Down) and Reset
- Top and Bottom Wraps
- Manual or Auto Turntable
- · Adjustable Turntable Speed
- · Adjustable Carriage Speed
- Film Carriage Auto, Manual Up, or Manual Down
- Adjustable Film Force
- Emergency Stop
- Integrated On/Off Switch
- Start Button

## PREMIUM FEATURES



### **Automatic Film Cut**

Automatically cutting the film at the end of the wrap cycle improves productivity up to 30%.



#### Select-Stretch

Select Stretch  $^{\text{TM}}$  allows you to quickly change your pre-stretch level from 230% to 270% with the press of a button.



## Safety Features

Control panel is keyed to prevent unauthorized access and will automatically power down when opened. The film carriage will safely stop if an obstruction is detected.



# Side-Mounted Carriage with Fast Film Feed

Side mounted carriage with Fast Film Feed for easy and quick film threading.



## High or Low Profile

Highlight will build the correct system for your application. The Predator XS is available in either High or Low Profile. The High Profile can be easily loaded with a fork lift. The Low Profile can use an optional ramp for loading with hand pallet jacks.

## SYSTEM SPECIFICATIONS

Pre-Stretch Gears	230% and 270% Selectable	Load Weight Capacity	Low & High Profile 4,000 pounds
Turntable	Low Profile 65" Diameter, 12 RPM High Profile 48"x48" Octagonal, 12 RPM	2 Wrap Modes	Spiral Up/Down and Spiral Up Only
Turntable Drive Motor	1/2 HP AC	Motors	AC (for lower maintenance)
Carriage Lift Motor	1/4 HP AC	Electrical Requirements	115 Volts, 15 Amp
Wrap Height	Up to 80 inches	Machine Weight	Low Profile 1,220 Pounds High Profile 1,500 Pounds

Contact:

